

# Spec Guide Issued June 2016



## **Statement of Line**

#### Work table | P2-10

#### Free standing type → P4







With front screen


With front and side screens

## L-shaped type $\rightarrow$ P5

\*Only the table top with a knife edge available.








With front screen

With front and side screens

#### Bench type → P6



#### Conference table | P11-12

#### 2-column table

Wide: 82 3/4", 94 1/2"



With cable opening

Wide: 82 3/4", 94 1/2"






Wide: 70 7/8"


Without cable opening

## 4-column table - wide type





## **Basic Table Specifications**




#### You can adjust the table top height within the range from 25 5/8" to 49 1/4".

\*With a safety reverse function that moves the desk approximately 1inch backward (approximately 11/8" when the desk is moved slowly) immediately when the desk hits an obstacle as standard \*Rated voltage: 100V, rated frequency: 50/60Hz \*Rated power consumption: free standing type: 300W L-shaped type: 450W bench type: 600W

When laying out tables, be sure to leave the amount of space indicated below between them to ensure safety. 3.5/8" 70" 72" 26 5/8 70" 70" 72' 70" 72"

Free standing type Bench type



## **Customizable Type**

#### ■Control panel







You can choose between three different types: the "button type (with the indicator)" including a height display and a memory function which allows you to save your preferred height, the simpler "button type (without the indicator)" which only includes a lifting and lowering button, and the "lever type" which allows you to lift or lower the desk more intuitively.

#### ■Table top edge





Knife edge

A sloped edge with a smooth, round surface that remains comfortable even if you lean on it with your arms. You can also select a more linear and sharper knife edge.



## Color

## ■Leg color



## ■Table top color







ZF97 White ZF96 Silver

ZF95 Black

MG07 White

MK17 Neo Wood Light MK18 Neo Wood Medium

MK19 Neo Wood Dark









#### Desk combination code

Combination		Part name / code	Combination		nation Part name / code		Combination Part name / code		Part name / code				
code		Table top	Body	code	code Table top		Body	code	code Table top		Body		
MY31	MG99	MG07 (Melamine: White)		MY21		MY21 MG99		MG07 (Melamine: White)		MY11	MG99	MG07 (Melamine: White)	
(White)	MG99	G939 (Edge: White)		(White)	MG99	G939 (Edge: White)		(White)	G939 (Edge: White)				
MY32	MK37	MK17 (Melamine: Neo Wood Light)		MY22 (Neo Wood Light)			MIZOZ	MK17 (Melamine: Neo Wood Light)		MY12	MK37	MK17 (Melamine: Neo Wood Light)	1
(Neo Wood Light)	IVINO	G947 (Edge: Neo Wood Light)	ZF97				G947 (Edge: Neo Wood Light)	ZF96	(Neo Wood Light)	IVINO1	G947 (Edge: Neo Wood Light)	ZF95	
MY33	MK38	MK18 (Melamine: Neo Wood Medium)	(White)	MY23		MK18 (Melamine: Neo Wood Medium)	(Silver)	MY13	MK38	MK18 (Melamine: Neo Wood Medium)	(Black)		
(Neo Wood Medium)	INIVOO	G948 (Edge: Neo Wood Medium)		(Neo Wood Medium)		G948 (Edge: Neo Wood Medium)		(Neo Wood Medium)	INIVOO	G948 (Edge: Neo Wood Medium)			
MY34	MK39	MK19 (Melamine: Neo Wood Dark)		MY24	MIZOO	MK19 (Melamine: Neo Wood Dark)		MY14 MY00	MIZOO	MK19 (Melamine: Neo Wood Dark)			
(Neo Wood Dark)	IVINJ9	G949 (Edge: Neo Wood Dark)		(Neo Wood Dark)	Wood Dark) MK39	G949 (Edge: Neo Wood Dark)		(Neo Wood Dark)	MK39	G949 (Edge: Neo Wood Dark)			

## ■Screen color

## Free standing type, L-shaped type Front and side screens (unicolor screen)

















F002 Sage

F015 Grape

F010 Pumpkin

F027 Chamomile

F025 Mushroom

F013 Blackberry

F007 Huckleberry

F029 Indigo

#### Free standing type, L-shaped type Front and side screens, two-tone cloth combination color \*Front and side screens only



Combination code	Cloth / outside					
F02B	F002 (Sage)					
F07B	F007 (Huckleberry)					
F10B	F010 (Pumpkin)					
F13B	F013 (Blackberry)					
F15B	F015 (Grape)					
F25B	F025 (Mushroom)					
F27B	F027 (Chamomile)					
F29B	F029 (Indigo)					




#### Bench type Fixed screen Color combination code


Combination code	Cloth	Body	Combination code	Cloth	Body	Combination code	Cloth	Body
FZT1	F002 (Sage)		FZS1	F002 (Sage)		FZR1	F002 (Sage)	
FZT2	F007 (Huckleberry)		FZS2	F007 (Huckleberry)		FZR2	F007 (Huckleberry)	
FZT3	F010 (Pumpkin)		FZS3	F010 (Pumpkin)		FZR3	F010 (Pumpkin)	
FZT4	F013 (Blackberry)		FZS4	F013 (Blackberry)		FZR4	F013 (Blackberry)	
FZT5	F015 (Grape)		FZS5	F015 (Grape)		FZR5	F015 (Grape)	
FZT6	F025 (Mushroom)	ZF97	FZS6	F025 (Mushroom)	ZF96	FZR6	F025 (Mushroom)	ZF95
FZT7	F027 (Chamomile)	(White)	FZS7	F027 (Chamomile)	(Silver)	FZR7	F027 (Chamomile)	(Black)
FZT8	F029 (Indigo)		FZS8	F029 (Indigo)	]	FZR8	F029 (Indigo)	



## **Free Standing Type**




\*Rated power consumption: 300W




#### ■Table

Con	Control panel		D	Н	Sloped edge	Knife edge						
Con					Item code	Item code						
		72"			3W20AA-MY	3W20FA-MY						
	with	66"		49 1/4"	3W20AB-MY	3W20FB-MY						
	indicator	60"	30"	₹	3W20AC-MY	3W20FC-MY						
	(C 00000C)	54"		25 5/8"	3W20AD-MY	3W20FD-MY						
Button		48"			3W20AE-MY	3W20FE-MY						
type		72"		49 1/4" 25 5/8"	3W20BA-MY	3W20GA-MY						
	without	66"			3W20BB-MY	3W20GB-MY						
	indicator	60"	30"		3W20BC-MY	3W20GC-MY□□						
		54"			3W20BD-MY	3W20GD-MY						
		48"			3W20BE-MY	3W20GE-MY						
		72"			3W20BF-MY	3W20GF-MY						
	without	66"		49 1/4"	3W20BG-MY	3W20GG-MY						
Lever type	indicator	60"	30"	. ≀	3W20BH-MY	3W20GH-MY						
Lype		54"		25 5/8"	25 5/8"	25 5/8"	25 5/8"	25 5/8"	25 5/8"	25 5/8"	3W20BJ-MY	3W20GJ-MY□□
		48"			3W20BK-MY□□	3W20GK-MY						

#### ■Screen (optional)



#### ■Clamp-free zone dimensions




## ■Required items and options

Item	Required / Option	Notes
Table	Required	
Screen	Option	Select according to the type of desk.
Cable guard	Option	Select single or double according to the cable capacitance.
Cable tray	Option	Select according to the type of desk.
Opposite table connector	Required depending on the conditions	Required when using an opposing layout.
Desktop power unit	Option	
Pedestal	Option	



## L-shaped Type





Knife edge

#### **■**Table

Contro	W	D	Н	Item code	
	with indicator	72"×72"			3W23PJ-MY□□
Putton type	(CO0000)	66"×66"			3W23PK-MY
Button type	without indicator	72"×72"	26 5/8"	49 1/4" 25 5/8"	3W23PL-MY□□
		66"×66"	20 3/6		3W23PM-MY
Lever type	without indicator	72"×72"			3W23PS-MY□□
		66"×66"			3W23PT-MY

## ■Screen (optional)


			Fro	ont		F	ront ar	nd sides
	28" / 317/8"			62 1/4" / 70 1/8" 62 1/4" / 70 1/8" 58 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	28" / 31 7/8"	6 1/4"		65 3/4" / 70 5/8" 65 3/4" / 20 5/8
Туре	W	Н	Т	Item code	W	Н	Т	Item code
17 3/4" Top	72"	31 7/8"	0.6"	3W61PJ-F	72"	31 7/8"	0.6"	3W60PJ-F□□□
surface	66"	31 7/0	0.0	3W61PK-F	66"	31 7/0	0.6	3W60PK-F
13 3/4" Top	72"	28"	0.6"	3W61PL-F	72"	28"	0.6"	3W60PL-F
surface	66"	20	0.0	3W61PM-F□□□	66"		0.0	3W60PM-F

## ■Required items and options

Item	Required / Option	Notes	
Table	Required		
Screen	Option	Select according to the type of desk.	
Cable guard	Option	Select single or double according to the cable capacitance.	
Cable tray	Option	Select according to the type of desk.	
Opposite table connector	Required depending on the conditions	Required when using an opposing layout.	
Desktop power unit	Option		
Pedestal	Option		



## **Bench Type**




#### ■Table

	Control panel				Sloped edge	Knife edge
Con			D	Н	Item code	Item code
		72"			3W22AA-MY□□	3W22FA-MY□□
	with	66"		49 1/4"	3W22AB-MY□□	3W22FB-MY
	indicator	60"	61 1/2"	1	3W22AC-MY	3W22FC-MY
	(C)0000	54"		25 5/8"	3W22AD-MY	3W22FD-MY
Button		48"			3W22AE-MY□□	3W22FE-MY
type		72"	61 1/2"	49 1/4" 25 5/8"	3W22BA-MY□□	3W22GA-MY□□
	without	66"			3W22BB-MY□□	3W22GB-MY□□
	indicator	60"			3W22BC-MY	3W22GC-MY□□
		54"			3W22BD-MY□□	3W22GD-MY□□
		48"			3W22BE-MY□□	3W22GE-MY□□
		72"			3W22BF-MY□□	3W22GF-MY□□
Ι.	without	66"		49 1/4"	3W22BG-MY□□	3W22GG-MY□□
Lever	indicator	60"	61 1/2"	1	3W22BH-MY□□	3W22GH-MY□□
1,50		54"		25 5/8"	3W22BJ-MY□□	3W22GJ-MY□□
		48"			3W22BK-MY□□	3W22GK-MY□□

<sup>\*</sup>With special cable guides (two pieces) \*Be sure to use a center panel for the desktop panel.

#### ■Fixed screen (optional)




#### ■Individual screen (optional)

	Front					Front and sides			
		46"~ 70" 150				31 7/8"	6"~ 70"		
Туре	W	Н	Т	Item code	W	Н	Т	Item code	
	70"			3W61GA-F□□□	70"			3W60GA-F	
17 3/4"	64"	1		3W61GB-F	64"			3W60GB-F□□□	
Тор	58"	31 7/8"	0.6"	3W61GC-F□□□	58"	31 7/8"	0.6"	3W60GC-F□□□	
surface	52"			3W61GD-F	52"			3W60GD-F	
	46"			3W61GE-F	46"			3W60GE-F□□□	
	70"			3W61HA-F	70"			3W60HA-F	
13 3/4"	64"			3W61HB-F	64"			3W60HB-F	
Тор	58"	28"	0.6"	3W61HC-F	58"	28"	0.6"	3W60HC-F	
surface	52"			3W61HD-F	52"		Ì	3W60HD-F	
	46"			3W61HE-F	46"			3W60HE-F	

<sup>\*</sup>Front panel and center panel cannot be used together.

## ■End cover (optional)



#### ■Required items and options

Item	Required / Option	Notes
Table	Required	
Screen	Option	Select according to the type of table. Only one can be selected.
End cover	Option	
Power source cable : Module kit	Required	Select one set for each desk according to the type of table.
Power source cablet : Receptacle	Required	Select a total of four for each desk according to the electrical circuit.
Power source cable : Power infeed	Required	Select one each according to the length of the required cable (from the floor to the starting position).
Wiring duct cover	Required	Select according to use of a center panel and type of desk.
Cable tray	Option	Select according to the type of desk.
Desktop power unit	Option	
Pedestal	Option	

<sup>●</sup>The dimensions are indicated in inch.



#### **Power Source Cable**

#### (1) Module kit for each width

W	Item code
For 72"	3P51AA-Y647
For 66"	3P51AB-Y647
For 60"	3P51AC-Y647
For 54"	3P51AD-Y647
For 48"	3P51AE-Y647

<sup>\*</sup>Select according to the table width. \*Order one set for each table set.

## (2) Receptacle


Circuit	Item code
1	3P11UP-Y708
2	3P11VP-Y708
3	3P11WP-Y708
4	3P11XP-Y708

<sup>\*</sup>Y708 (Black)

#### (3) Hardwire power infeed

W	Item code
240"	3P11LP-Y647
120"	3P11MP-Y647
72"	3P11NP-Y647

#### (4)Wiring duct cover



<sup>\*</sup>ZF97 (White), ZF96 (Silver), ZF95 (Black)

## **Electrical Diagram**

- Utilizes 8-wire, 4-circuit electrical module system as power source for each outlet in wiring duct.
- For every power infeed of 4-circuit electrical module system a 3 + 1 configuration is available as standard.
- All electrical module systems need to be installed in field with the back-to-back height adjustable table by furniture installer.
- 20-amp hardwire power infeed only. A licensed electrician is required to complete hardwire connections to building's power source.
- Hardwire power infeed is having 3 length(72"/120"/240") as standard. Other length hardwire power infeed is available as an option.
- Hardwire power infeed is flexible metal conduit as standard. Liquid-tight conduit option available.
- Neutral(White) wires are 10 gauge, hot and ground wires are 12 gauge
- When specify, receptacles must be specified separately.
- Power source cables and desktop power outlets are UL listed for upholding strict safety standards.

## Chicago Electrical Requirements

The city of Chicago may require hardwiring of electrical components. For Chicago applications, please contact your local representatives or dealerships.

#### **Other Municipality Electrical Requirements**


Other metropolitan areas besides Chicago may have special electrical requirements as well. Consult a local electrical contractor for proper code compliance information.

Circuit 1 Circuit 2 Circuit 3 Circuit 4 Electrical diagram for Hardwire Power infeed. Gray Neutral 2 White Neutral 1 Green/Yellow Iso Ground Green Ground Pink Hot 4 Blue Hot 3 Red Hot 2 Black Hot 1

<sup>\*</sup>Order 4 receptacles for each module kit.




## **Cable Routing Diagram**







## **Effective Dimensions From The Leg To The Duct**



## **Power Infeed Floor Entry Location**



## **Clamp-free Zone Dimensions**




Area where clamping is possible with individual screen.



## **Options**

#### ■Cable guard (Free standing type / L-shaped type)



Single duct type cable guard


3W641Y-ZF□□

Double duct type cable guard 3W646Y-ZF□□

ZF95 (Black) ZF96 (Silver) ZF97 (White)

\*Prepare a cable with a length of 59".

#### ■Cable tray (large-capacity type)



<sup>1</sup> piece / set G473 (Black)

#### ■Opposite table connector



For Free standing and L-shaped typs

3W971Y-G ...

2 pieces / set

When laying out desks opposite each other, attach these couplings to the end legs. Please order enough couplings for the number of end legs you wish to connect.

G975 (Neo White) G204 (Black) G636 (Skip Gray)

#### ■Desktop power unit



Power×3 3P13AY-Y707 Cable length:120" Y707 (White)



Power×2, USB×2 3P13BY-Y707 Cable length:120" Y707 (White)

#### ■Pedestal



Pedestal side handgrip 3W33AA-Z□□□

15 3/8"W×22 7/8"D×22 1/8"H



Pedestal front handgrip 3WC3AA-Z□□□

15 3/8"W×22 7/8"D×22 1/8"H

Inside dimensions: Upper Pen tray drawer 12 1/2"W×17 5/8"D×1 5/8H, Center Ordinary drawer 12 1/2"W×17 1/4"D×7"H, Lower filing drawer (A4 size) 12 1/2"W×20 1/2"D×10 3/8"H

Common specifications: An all-locking key (with lock / release display), caster stoppers, rollers for overturning prevention, a latch. Each filing drawer or ordinary drawer has one partition plate.

Common colors: Z25 (Black), Z637 (Skip Silver), Z975 (Neo White)



15 3/8"W×22 7/8"D×15 3/4"H

With two partition plates and a latch (filing drawer), an all-locking key (with lock / release display), caster stoppers, rollers for overturning prevention



Stool pedestal With a drawer + a pen tray, side handgrip 3W31BX-Z□□□

15 1/2"W×22 7/8"D×17 3/8"H

With two partition plates, a latch (filing drawer), an all-locking key (with lock / release display), caster stoppers, rollers for overturning prevention, a pen tray drawer (inside dimensions: 12 1/2"W×17 5/8"D×1 5/8H), a B4/A4 filing drawer (inside dimensions: 12 1/2"W× 20 1/2"D×11 1/2"H)


<sup>\*</sup>Replace the cable tray included in the desk (standard type) with this tray. This tray cannot be used together with the standard type.

\*The lowest height of the desk table top when the special SW wagon is used is



## Conference-table


#### **Basic Table Specifications**



The tabletop height of the meeting table can be adjusted within the range from 27 5/8" to 49 1/4".

\*With a safety reverse function that moves the desk approximately 1inch backward (approximately 1 1/8" when the desk is moved slowly) immediately when the desk hits an obstacle as standard \*Rated voltage 100 V, rated frequency 50/60Hz \*Rated power consumption: 300W

#### **Basic Table Specifications (wide type)**



4-column table [wide type]

The tabletop height of the meeting table (wide type) can be adjusted within the range from 27 5/8" to 49 1/4".

\*With a safety reverse function that moves the desk approximately 1inch backward (approximately 1 1/8" when the desk is moved slowly) immediately when the desk hits an obstacle as standard \*Rated voltage 100 V, rated frequency 50/60 Hz \*Rated power consumption: 600W

#### ■Control panel







You can choose between three different types: the "button type (with the indicator)" including a height display and a memory function which allows you to save your preferred height, the simpler "button type (without the indicator)" which only includes a lifting and lowering button, and the "lever type" which allows you to lift or lower the desk more intuitively.

## ■Four tabletop colors



The entire circumference is equally curved. The molded resin structure gives the surface a soft feel.

#### ■Cable opening



The cable cover can be opened and closed. A spacious opening allows you to store power strips and similar equipment inside. When not using the cable duct, use the cover to close it completely.

#### Color

\*Common with the wide type

#### ■Leg color



## ZF95 Black





■Table top color







MK19 Neo Wood Dark

MG07 White MK17 Neo Wood Light MK18 Neo Wood Medium

#### Table combination code


Combination		Part name / code		Combination		Part name / code		Combination		Part name / code			
	code Table top Body		code	Table top		Body	code	Table top E		Body			
	MY30	MY01	MG07 (Melamine: White)			MY20	MY01	MG07 (Melamine: White)		MY10 MYC	MY01	MG07 (Melamine: White)	
	(White)	IVITOI	GC70 (Edge: Pale Gray)		(White)	e)   MYUT	GC70 (Edge: Pale Gray)		(White)	INITOT	GC70 (Edge: Pale Gray)		
	MY32	MK37	MK17 (Melamine: Neo Wood Light)	17 (Melamine: Neo Wood Light) MY22 MK37 MK17 (Melamine: Neo	MK17 (Melamine: Neo Wood Light)		MY12	MK37	MK17 (Melamine: Neo Wood Light)	]			
(Ne	eo Wood Light)	t) IVINO	G947 (Edge: Neo Wood Light)	ZF97	(Neo Wood Light)	) IVINO	G947 (Edge: Neo Wood Light)	ZF96	(Neo Wood Light)	IVINO	G947 (Edge: Neo Wood Light)	ZF95	
	MY33	MK38 MK18 (Melamine: Neo Wood Medium)  G948 (Edge: Neo Wood Medium)	(White)	MY23	MK38	MK18 (Melamine: Neo Wood Medium)	(Silver)	MY13 MK20	MK38	MK18 (Melamine: Neo Wood Medium)	(Black)		
(Ne	o Wood Medium)		G948 (Edge: Neo Wood Medium)		(Neo Wood Medium)	o Wood Medium)	G948 (Edge: Neo Wood Medium)		(Neo Wood Medium)	INILYOO	G948 (Edge: Neo Wood Medium)		
	MY34	MICOO	MK19 (Melamine: Neo Wood Dark)		MY24	MY24 MK39	MK19 (Melamine: Neo Wood Dark)		MY14 MKOC	MK39	MK19 (Melamine: Neo Wood Dark)		
(Neo Wood Dark)	k) MK39	G949 (Edge: Neo Wood Dark)		(Neo Wood Dark)	ark) IVIK39	G949 (Edge: Neo Wood Dark)		(Neo Wood Dark)	IVINOS	G949 (Edge: Neo Wood Dark)			



## Conference-table


## 2-column Table

## With cable opening



<sup>\*</sup>The 94 1/2" and 82 3/4" models have two cable openings, and the 70 7/8" model has one cable opening.


#### Without cable opening



\*Rated power consumption: 300W



Sloped edge






#### ■Required items and options

Item	Required / Option		
Table	Required		
Vertical cable guard	Option		

## 4-column Table (wide type)

#### With cable opening



47 1/4"	141 3/4"	
27 5/8" ~ 49 1/2		*Rated power consumption: 600W

Cable opening	Co	ntrol panel	W	D	Н	Item code
		with indicator	141 3/4"	47 1/4"	49 1/4" 27 5/8"	3W27KA-MY□□
	Button type		118 1/8"			3W27KB-MY□□
Yes		without indicator without indicator	141 3/4"			3W27LA-MY□□
res			118 1/8"			3W27LB-MY□□
	Lever type		141 3/4"			3W27LF-MY□□
			118 1/8"			3W27LH-MY□□
	Button type	With Indicator	141 3/4"	47 1/4"	49 1/4" 27 5/8"	3W27KD-MY□□
			118 1/8"			3W27KE-MY□□
No		without indicator	141 3/4"			3W27LD-MY□□
			118 1/8"			3W27LE-MY□□
	Lever type	without indicator	141 3/4"			3W27LK-MY□□
			118 1/8"			3W27LL-MY□□

\*With integraded cable guides

OKAMURA CORPORATION

International Sales & Marketing Div. 2-14-27, Akasaka, Minato-ku, Tokyo 107-0052, JAPAN Tel: +81-3-5561-4085 Fax: +81-3-5561-4086 http://www.okamura.jp/ The products listed in this spec guide are available as of June 2016. Please note that specifications, dimensions, and colors are subject to change without notice. The colors of the actual products may differ somewhat from the colors shown in the spec guide depending on printing conditions.